

PRODUCT DATA SHEET

Lubricants – Industrial

Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, **HYUNDAI XTeer** created by Hyundai's built-up technology will open the new world of Industrial lubricants.

XTeer Grease Moly EP 2

Description

XTeer Grease Moly EP 2 is high performance lithium grease with special EP additive of MoS₂. It is suitable for general service and application needed EP anti-wear protection. As it is manufactured by using high-refined base oils and various high performance additives, it provides outstanding lubrication for many applications subjected to excellent extreme pressure, oxidation stability, and anti-wear property.

Application

- ✧ All sorts of bearings operated under boundary lubrication regime.
- ✧ Pin / Bush and open gear applications, especially in construction and mining equipment.
- ✧ Any machinery parts needed EP and anti-wear protection.

Features / Benefits

- ✧ Excellent resistance for the shock (extreme pressure) loading.
- ✧ Good oxidation stability
- ✧ Service temperature: -20°C ~ +140°C

Typical Properties



XTeer Grease Moly EP 2		Test Method
Thickener	Lithium	
Worked Penetration (25°C)	280	ASTM D 217
Dropping Point (°C)	229	ASTM D 566
MoS ₂ (wt.%)	3	
Service temperature	-20°C ~ +140°C	