

PRODUCT DATA SHEET

Lubricants – Engine Oil - Passenger Car Motor Oils

“PLEASURE” the emotion you can experience with HYUNDAI XTeer, based on HYUNDAI’s most advanced technology from KOREA representing the next generation of automobile lubricants.

XTeer TOP 5W30

Description

XTeer TOP is a premium performance engine oil formulated from 100% synthetic base fluids. It is fully suitable for use in passenger car and light truck gasoline engines, passenger car diesel engines and passenger car LPG engines under all operating conditions. The wider temperature range capability of the synthetic base fluid ensures correct oil viscosity which reduces friction at start-up and provides maximum lubrication during high temperature operation in all seasons. The effective anti-wear additive system reduces wear by protecting surfaces when load causes breakdown of the lubricant film.

Application

- ✧ Naturally aspirated gasoline engines
- ✧ LPG and diesel engines in passenger cars
- ✧ Light truck gasoline and diesel engines
- ✧ Recommended for use in gasoline and diesel powered RVs and SUVs
- ✧ Passenger cars with high speed, four-stroke, turbocharged and DPF / CPF



SAE		5W30
Viscosity	40°C	68.81
	100°C	11.48
Viscosity Index		162
Flash Point (°C)		226
Pour Point (°C)		-35

Features / Benefits

- ✧ It provides maximum engine protection at the highest speeds
- ✧ It maximizes the engine performance in the toughest conditions Low foaming
- ✧ It reduces deposit and sludge in turbocharged engines by more than 50%
- ✧ It reduces deposit and sludge in engines and pistons
- ✧ Tested with all rubber seals in the engine

Remarks

XTeer TOP 5W30 meets or exceeds the requirements of

- ✧ **API SN**
- ✧ **ACEA C3-16**

- ◇ MB-Approval 229.31/229.51/229.52
- ◇ BMW Longlife – 04
- ◇ GM dexos 2
- ◇ VW 502 00/505 01