

# SAFETY DATA SHEET

# According to OSHA Hazcom Standard 29 CFR 1910.1200

# XTeer SO 3005 (ENG)

Date of issue: 2016-10-27	Revision date: Not applicable	Version: 2.0
1. IDENTIFICATION		
A. Product name		
- XTeer SO 3005 (ENG)		
B. Recommended use and re	estriction on use	
- General use	: Marine System Oil	
- Restriction on use	: Do not use for purposes other than recommended.	
C. Manufacturer / Supplier	/ Distributor information	
$\circ$ Manufacturer information	n	
- Company name	: HD HYUNDAI OILBANK	
- Address	: 17-10, Mabuk-ro 240beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea	
- Emergency telephone number	: 02-500-4500	
<ul> <li>Supplier/Distributer info</li> </ul>	rmation	
- Company name	: HD HYUNDAI OILBANK	
- Address	: 17-10, Mabuk-ro 240beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea	
- Emergency telephone number	: 02-500-4500	

# 2. HAZARD IDENTIFICATION

# A. GHS Classification

- Acute toxicity (dermal) : Category5
- Acute toxicity (inhalation: vapor) : Category4
- Carcinogenicity : Category1B
- Acute aquatic toxicity : Category3

## **B. GHS label elements**

• Hazard symbols



Signal words

- Danger

- Hazard statements
  - H313 May be harmful if contact with skin.
  - H332 Harmful if inhaled
  - H350 May cause cancer
  - H402 Harmful to aquatic organisms.

# • Precautionary statements

#### 1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

### 2) Response

- P302+P312 IF ON SKIN: Call a POISON CENTER/doctor if you feel unwell.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.

# 3) Storage

- P405 Store locked up.

# 4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

## C. Other hazards which do not result in classification

- Not available

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Distillates (petroleum), hydrotreated heavy paraffinic	Emulsifiable oil	64742-54-7	96.83
Residual oils (petroleum), hydrotreated	Not available	64742-57-0	2.4
Phosphorodithioic acid O,O- dialkyl(C=1-14) esters zinc salts	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts ; Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts ; PHOSPHORODITHIOIC ACID, O,O-DI(C1-14)-ALKYL ESTERS ZINC SALT ; DI-C1-14 ALKYL DITHIOPHOSPHORIC ACID, ZINC SALT ; PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS,ZINC SALTS ; Dialkyl(C1-C14)dithiophosphoric acid, zinc salt ; Phosphorodithioic acid, O,O-di-C1-14-alkyl ester, zinc salt ; Zinc, O,O-di(C1-14)-alkylphosphorodithioate ;	68649-42-3	0.66
Phenol, (tetrapropenyl) derivs.	(TETRAPROPENYL)-PHENOL	74499-35-7	0.05
Distillates (petroleum), solvent- dewaxed light paraffinic	Solventdewaxed light paraffinic distillate (petroleum)	64742-56-9	0.03
1,2-Ethanediol	1,2-Dihydroxyethane ; Ethylene alcohol ; Ethylene dihydrate ; 2- Hydroxyethanol ; Ethane-1,2-diol ; Monoethylene glycol ;	107-21-1	0.02
Methylbenzenesulfonic acid, mono(C=20~28)-branched alkyl derivs., calcium salt	Not available	722503-70-0	0.02

# 4. FIRST AID MEASURES

# A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

## B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.
- Remove contaminated clothing, shoes and isolate.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

#### C. Inhalation contact

- Take specific treatment if needed.
- When exposed to large amounts of steam and mist, move to fresh air.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

#### **D. Ingestion contact**

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

# E. Delayed and immediate effects and also chronic effects from short and long term exposure

#### - Not available

## F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

# **5. FIREFIGHTING MEASURES**

#### A. Suitable (Unsuitable) extinguishing media

- Avoid use of water jet for extinguishing
- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

#### B. Specific hazards arising from the chemical

- Harmful if inhaled
- Harmful to aquatic organisms.
- May be harmful if contact with skin.
- May cause cancer

#### C. Special protective actions for firefighters

- Avoid inhalation of materials or combustion by-products.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Keep unauthorized personnel out.

# 6. ACCIDENTAL RELEASE MEASURES

#### A. Personal precautions, protective equipment and emergency procedures

- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Move container to safe area from the leak area.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

## **B.** Environmental precautions

- If large amounts have been spilled, inform the relevant authorities.
- Prevent runoff and contact with waterways, drains or sewers.

## C. Methods and materials for containment and cleaning up

- Appropriate container for disposal of spilled material collected.
- Dike for later disposal.
- Disposal of waste shall be in compliance with the Wastes Control Act
- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.

# 7. HANDLING AND STORAGE

# A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Avoid direct physical contact.
- Comply with all applicable laws and regulations for handling
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.

# B. Conditions for safe storage, including any incompatibilities

- Avoid direct sunlight.

- Check regularly for leaks.
- Do not apply any physical shock to container.

- Do not apply direct heat.

- Do not use damaged containers.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

# • ACGIH TLV

- [Distillates (petroleum), hydrotreated heavy paraffinic]: TWA 5 mg/m3, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)

- [Residual oils (petroleum), hydrotreated] : TWA 5 mg/m3, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)

- [Distillates (petroleum), solvent-dewaxed light paraffinic]: TWA 5 mg/m3, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)

- [1,2-Ethanediol] : TWA 25 ppm, STEL 50 ppm (10 mg/m3)

#### • OSHA PEL

- Not applicable

# **B.** Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

# C. Individual protection measures, such as personal protective equipment

- Respiratory protection
  - Any air-purifying respirator with a full facepiece and an organic vapor canister.
  - Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
  - Any chemical cartridge respirator with organic vapor cartridge(s).
  - Consider warning properties before use.

- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

- Respiratory protection is ranked in order from minimum to maximum.
- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.

## • Eye protection

- Provide an emergency eye wash station and quick drench shower in the immediate work area.
- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Hand protection
  - Wear appropriate chemical resistant glove.
- Skin protection

- Wear appropriate chemical resistant protective clothing.

- Others
  - Not available

# 9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid
- Color	Amber
B. Odor	mild
C. Odor threshold	Not Available
D. pH	Not available
E. Melting point/Freezing point	Not Available
F. Initial Boiling Point/Boiling Ranges	Not available
G. Flash point	> 250°C
H. Evaporation rate	Not Available
I. Flammability(solid, gas)	Not Available
J. Upper/Lower Flammability or explosive limits	Not Available
K. Vapour pressure	Not Available
L. Solubility	Not Available
M. Vapour density	Not Available
N. Specific gravity(Relative density)	0.868
O. Partition coefficient of n-octanol/water	Not Available

P. Autoignition temperature	Not Available
Q. Decomposition temperature	Not Available
R. Viscosity	11.9 cSt @100°C
S. Molecular weight	Not Available

# **10. STABILITY AND REACTIVITY**

# A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

#### **B.** Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

## C. Conditions to avoid

- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with incompatible materials and condition.

#### **D.** Incompatible materials

- Not available

#### E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

### **11. TOXICOLOGICAL INFORMATION**

## A. Information on the likely routes of exposure

- $\circ \ {\rm Respiratory} \ {\rm tracts}$
- Not available
- Oral
  - Not available

# ○ Eye·Skin

- Not available

## B. Delayed and immediate effects and also chronic effects from short and long term exposure

## • Acute toxicity

- \* Oral
  - Product (ATEmix) : >5000mg/kg
  - [Distillates (petroleum), hydrotreated heavy paraffinic] : LD50 > 5000 mg/kg Rat (ECHA)
  - [Residual oils (petroleum), hydrotreated] : LD50 >5000 mg/kg Rat (OECD Guideline 401 (Acute Oral Toxicity), GLP) (ECHA)
  - [Distillates (petroleum), solvent-dewaxed light paraffinic] : LD50 > 5000 mg/kg Rat (ECHA)
  - [1,2-Ethanediol]: LD50 300~2000 mg/kg (EU Harmonized Cat. 4) (ECHA)

# \* Dermal

- Product (ATEmix) : 2000mg/kg < ATEmix <= 5000mg/kg
- [Distillates (petroleum), hydrotreated heavy paraffinic]: LD50 >5000 mg/kg Rabbit (ECHA)
- [Residual oils (petroleum), hydrotreated] : LD50 >2000 mg/kg Rabbit (OECD Guideline 402 (Acute Dermal Toxicity), GLP) (EHCA)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : LD50 > 2000 mg/kg Rabbit (OECD Guideline 402 (Acute Dermal Toxicity),GLP) (EHCA)
- [1,2-Ethanediol] : LD50 > 3500 mg/kg Mouse (ECHA)

#### \* Inhalation

- Product (ATEmix) : 10.0mg/L 4hr < ATEmix <= 20.0mg/L 4hr
- [Distillates (petroleum), hydrotreated heavy paraffinic] : Aerosol LC50 > 5.53 mg/L 4 hr, Kat, Read-across : CAS No. 64/41-88-4 (FCHA)
- [Residual oils (petroleum), hydrotreated] :  $LC50 > 2.18 \text{ mg/}\ell 4 \text{ hr Rat}$  (OECD Guideline 403 (Acute Inhalation Toxicity), GLP) (ECHA)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : Aerosol LC50 2.18  $mg/\ell$  4 hr Rat (OECD TG 403, GLP) (ECHA)
- [1,2-Ethanediol] : Aerosol LC50 > 2.5 mg/L 6 hr(conversion to > 3.75 mg/L 4 hr )Rat (ECHA)

## $\circ$ Skin corrosion/irritation

- Not available

# • Serious eye damage/irritation

- Not available
- Respiratory sensitization

### - Not available

- Skin sensitization
- Not available
- Carcinogenicity

## \* IARC

- Not available

#### \* OSHA

- Not available

# \* ACGIH

- [1,2-Ethanediol]: A4

## \* NTP

- Not available
- \* EU CLP
  - [Distillates (petroleum), hydrotreated heavy paraffinic] : Carc. 1B (Note L)
  - [Residual oils (petroleum), hydrotreated] : Carc. 1B (Note L)
  - [Distillates (petroleum), solvent-dewaxed light paraffinic] : Carc. 1B (Note L)

#### ◦ Germ cell mutagenicity

#### - Not available

• Reproductive toxicity

#### - Not available

• STOT-single exposure

#### - Not available

- STOT-repeated exposure
  - Not available

# • Aspiration hazard

- Not available

### **12. ECOLOGICAL INFORMATION**

## A. Ecotoxicity ° Fish

- [Distillates (petroleum), hydrotreated heavy paraffinic] : LL50 > 100 mg/L, 96hr, Pimephales promelas (ECHA)
- [Residual oils (petroleum), hydrotreated] : (Insoluble substances, water solubility 1 mg/ℓ or less (Not classified in acute toxicity)) (Estimate)
- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts]: LC50 1 ~ 5 mg/ℓ 96 hr Pimephales promelas (ESIS)
- [Phenol, (tetrapropenyl) derivs.] : LC50 0.146 mg/l 96 hr (Estimate)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : LC50 5000 mg/l 96 hr Oncorhynchus mykiss (IUCLID)
- [1,2-Ethanediol]: LC50 >72860 mg/ℓ 96 hr Pimephales promelas, NOEC 15380 mg/ℓ 7 d Pimephales promelas (ECHA)

#### • Crustaceans

- [Distillates (petroleum), hydrotreated heavy paraffinic]: EL50 > 10000 mg/L, 48hr, Daphnia magna (ECHA)
- [Residual oils (petroleum), hydrotreated] : (Regulation EC No. 1272/2008, Insoluble substances, water solubility 1 mg/ $\ell$  or less (Not classified
- in acute toxicity) water solubility: 0.0001411) (Estimate)
- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : EC50 1 ~ 1.5 mg/ℓ 48 hr Daphnia magna (ESIS)
- [Phenol, (tetrapropenyl) derivs.]: LC50 0.177 mg/ℓ 48 hr (Estimate)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : EC50 1000 mg/ℓ 48 hr Daphnia magna (IUCLID)
- [1,2-Ethanediol] : EC50 >100 mg/ℓ 48 hr Daphnia magna (OECD TG 202, GLP), NOEC 8590 mg/L 7 d Ceriodaphnia dubia (ECHA)

## Algae

- [Distillates (petroleum), hydrotreated heavy paraffinic] : EC25 1152.9 mg/L, 96hr, Pseudokirchneriella subcapitata, NOEL >= 100 mg/L, 72hr (ECHA)
- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : EC50 1 ~ 5 mg/ℓ 96 hr Selenastrum capricornutum (ESIS)
- [Phenol, (tetrapropenyl) derivs.]: EC50 0.6 mg/ℓ 96 hr (Estimate)
- [1,2-Ethanediol] : EC50 6500 ~ 13000 mg/l 96 hr Raphidocelis subcapitata (EPA 600/9-78-018) (ECHA)

## B. Persistence and degradability

#### Persistence

- [Distillates (petroleum), hydrotreated heavy paraffinic] : log Pow = 1.99 ~ 18.02 (20°C) (ECHA)
- [Residual oils (petroleum), hydrotreated] : log Kow 8.81 (Estimate)
- [Phenol, (tetrapropenyl) derivs.] : log Kow = 5.12 (Estimate)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : log Kow 3.9 ~ 6 (Estimate)

### - [1,2-Ethanediol] : log Pow -1.36 (ECHA)

# Degradability

- [Distillates (petroleum), solvent-dewaxed light paraffinic] : (non-degradable, BIOWIN 1,2,5,6,7) (Estimate)

# C. Bioaccumulative potential

# • Bioaccumulative potential

- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : BCF 3.162 (Estimate)
- [Phenol, (tetrapropenyl) derivs.] : BCF = 1111 (Estimate)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : BCF 5151 (L/kg wet-wt ) (Estimate)

#### o Biodegradation

- [1,2-Ethanediol] : DOC removal 90 ~ 100 % degradation, 10 d Readily biodegradable (ECHA)

## D. Mobility in soil

- Not available

#### E. Other adverse effects

- [Residual oils (petroleum), hydrotreated] : Hardly soluble substances. Acute toxicity is not classified because the water solubility is less than 1 mg/L (Water solubility: 0.0001411). (Estimate)

### **13. DISPOSAL CONSIDERATIONS**

#### A. Disposal methods

- It shall be treated by incineration

- Oil water separation technology shall be applied as pre-waste treatment if it is applicable

- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them

#### **B.** Special precautions for disposal

Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
Dispose of waste in accordance with all applicable laws and regulations.

#### **14. TRANSPORT INFORMATION**

### A. UN No. (IMDG CODE/IATA DGR)

- Not applicable

## **B.** Proper shipping name

- Not applicable

# C. Hazard Class

- Not applicable

## D. IMDG CODE/IATA DGR Packing group

- Not applicable

### E. Marine pollutant

- Not applicable

### F. Special precautions for user related to transport or transportation measures

- Air transport(IATA): Not subject to IATA regulations.

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : Not available
- EmS SPILLAGE SCHEDULE : Not available

## **15. REGULATORY INFORMATION**

#### A. National and/or international regulatory information

#### • POPs Management Law

- [Distillates (petroleum), hydrotreated heavy paraffinic] : Not applicable

- [Residual oils (petroleum), hydrotreated] : Not applicable
- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : Not applicable
- [Phenol, (tetrapropenyl) derivs.] : Not applicable
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : Not applicable
- [1,2-Ethanediol] : Not applicable
- [Methylbenzenesulfonic acid, mono(C=20~28)-branched alkyl derivs., calcium salt] : Not applicable

# $\circ$ Information of EU Classification

## \* Classification

- [Distillates (petroleum), hydrotreated heavy paraffinic] : H350
- [Residual oils (petroleum), hydrotreated]: H350
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : H350
- [1,2-Ethanediol]: H302

## $\circ$ U.S. Federal regulations

## \* OSHA PROCESS SAFETY (29CFR1910.119)

- Not applicable
- \* CERCLA Section 103 (40CFR302.4)
  - [1,2-Ethanediol] : 2267.995 kg 5000 lb
- \* EPCRA Section 302 (40CFR355.30)
  - Not applicable
- \* EPCRA Section 304 (40CFR355.40)

- Not applicable

## \* EPCRA Section 313 (40CFR372.65)

- [1,2-Ethanediol] : Applicable

 $\circ$  Rotterdam Convention listed ingredients

```
- Not applicable
```

# $\circ$ Stockholm Convention listed ingredients

- Not applicable

Montreal Protocol listed ingredients

- Not applicable

## **16. OTHER INFORMATION**

## A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

## B. Issue date

- 2016-10-27

## C. Revision number and Last date revised

- Not applicable

# D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).