

HYUNDAI XTeer G500

A PRODUCT OF HYUNDAI XTEER CONSUMER MARKETS, A COMMERCIAL UNIT OF HYUNDAI OILBANK



HYUNDAI XTeer Lubricants

ALWAYS MOVING TOGETHER

<https://hyundaixteer.com/en>


The Only One – Endorsed and recommended by HYUNDAI OILBANK



Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, HYUNDAI XTeer created by Hyundai's built-up technology will open the new world of Industrial lubricants.

HYUNDAI XTeer G500 motor oil contains a proprietary blend of high-quality base oils and advanced additive technology to help you achieve peak performance from your machine. Developed to protect engines and wet clutch systems in high RPM and high temperature conditions to maximize power and smooth shifting.

** Oil recommendations differ per OEM brand. Check owner's manual before use.*



Performance levels

API SL

**SAE 5W-30, 10W-30, 10W-40
15W-40, 20W-50**




Features and benefits

**Excellent sludge protection
Prevents engine leaks and high oil consumption
Outstanding wear protection
Maximum horsepower**



Applications

**All gasoline vehicles
The vehicles which need the requirement of API SL oil.**



HYUNDAI XTeer G500

A PRODUCT OF HYUNDAI XTEER CONSUMER MARKETS, A COMMERCIAL UNIT OF HYUNDAI OILBANK



HYUNDAI XTeer Lubricants

ALWAYS MOVING TOGETHER


xteer.co.kr/eng

The Only One – Endorsed and recommended by HYUNDAI OILBANK



Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, HYUNDAI XTeer created by Hyundai's built-up technology will open the new world of Industrial lubricants.

| SAE | Density | Kinematic Viscosity | | Viscosity Index | Flash Point | Pour Point | C.C.S | TBN |
|--------|---------|---------------------|-------|-----------------|-------------|------------|----------------|-----|
| | | 40°C | 100°C | | | | | |
| 5W-30 | 0.8595 | 62.89 | 10.13 | 148 | 226 | -42.0 | 6,402 (@-30°C) | 6.2 |
| 10W-30 | 0.8738 | 75.3 | 10.9 | 133 | 230 | -43.0 | 6,560 (@-25°C) | 6.2 |
| 10W-40 | 0.8654 | 97.1 | 13.7 | 143 | 254 | -43.0 | 5,808 (@-25°C) | 6.2 |
| 15W-40 | 0.8684 | 115.7 | 14.9 | 133 | 240 | -36.0 | 6,121 (@-20°C) | 6.2 |
| 20W-50 | 0.8735 | 160.6 | 18.7 | 125 | 260 | -33.0 | 6,700 (@-15°C) | 6.2 |



STI –Stop Time Index: how quickly the clutch engages
 SFI –Static Friction Index: torque required to cause clutch to slip when fully engaged
 DFI –Dynamic Friction Index: how the clutch engages when already spinning

HIGHER IS BETTER

XTeer G500 is formulated from Synthetic Technology meeting the requirement of current advanced top-tier engine oil grade of API SL. It is optimized to provide complete passenger car engine oil performance especially for fuel efficiency, reducing friction loss and durability.

* Oil recommendations differ per OEM brand. Check owner's manual before use.