

XTEER AW

Industrial Lubricants – Hydraulic fluid

Description

XTeer AW is the best anti-wear hydraulic oil. It is formulated with excellent quality base oil technology and an additive system that provides exceptional oxidation stability, water separability and foam suppression. It is especially exceptional for anti-wear protection.

Application

Recommended for applications calling for anti-wear, rust and oxidation inhibited Additives including

- ✧ Hydraulic systems
- ✧ Industrial bearings
- ✧ Circulating systems, splash, bath and ring lube systems for bearings and gears

Features / Benefits

- ✧ Protection against oxidation
- ✧ Protection against rust and corrosion
- ✧ Outstanding wear protection.

Specification

XTeer AW meets or exceeds the requirements of

- Bosch Rexroth RDE 90235
- Parker Denison HF-0, HF-1, HF-2
- DIN 51524 Part 2
- ISO 11158 HM
- Eaton E-FDGN-TB002-E
- Fives Cincinatti P-68, P-69, P-70
- GB 11118.1-2011, L-HM
- JCMAS P041 HK Hydraulic specification
- ASTM D6158, HM
- SAE MS 1004, HM
- GM LS 2
- AIST 126, 127
- SEB 181222

Product Name	Specific Gravity (15°C/4°C)	Kinematic Viscosity (cSt)		Viscosity Index	Flash Point (°C)	Pour Point (°C)
		@40°C	@100°C			
XTeer AW VG 15	0.8565	16.45	3.57	96	194	-33.0
XTeer AW VG 22	0.8576	22.98	4.38	104	194	-42.0
XTeer AW VG 32	0.8592	31.17	5.37	106	220	-27.0
XTeer AW VG 37	0.8586	37.52	6.09	108	242	-38.0
XTeer AW VG 46	0.8627	44.93	6.83	107	234	-30.0
XTeer AW VG 68	0.8663	64.39	8.62	106	244	-36.0
XTeer AW VG 100	0.8685	94.31	11.06	104	232	-24.0
XTeer AW VG 150	0.8693	147.1	15.34	106	266	-18.0