



XTEER IGO EP

Industrial Lubricants - Gear Oil

Description

XTeer IGO is an outstanding Industrial Gear Oil. It is formulated with excellent quality base oil technology and extreme pressure (EP) additives. It is especially designed to provide great protection against high loads, prevent damage on tooth- and friction surfaces.

Application

Recommended for Enclosed industrial gear drives operating under heavy loads, high peak loads or intermittent shock loads

- ♦ Enclosed spur, bevel, helical, herringbone and planetary gear drives
- ♦ AGMA EP gear
- ♦ Heavily loaded plain

Features / Benefits

- High load-carrying capacity for protection against scuffing and wear
- ♦ Excellent oxidation resistance and thermal stability
- ♦ Excellent deposit control for gearbox cleanliness
- ♦ Protects against rust and corrosion
- ♦ Fast water separation
- ♦ Quick foam release

Specification

XTeer IGO EP meets or exceeds the requirements of

♦ US Steel 224

AGMA 9005-E02

♦ ISO 12925-1 CKC/CKD

DIN 51517 Part 3

Product Name	Specific Gravity	Kinematic (cs	•	Viscosity	Flash Point	Pour Point	Cu corrosion
	(15°C/4°C)	@40°C	@100℃	Index	(°C)	(°C)	(@100°C, 3Hr)
XTeer IGO EP VG 68	0.8647	69.77	9.233	108	244	-36	1a
XTeer IGO EP VG 100	0.8728	100.5	11.6	103	248	-34	1a
XTeer IGO EP VG 150	0.8707	142.4	15.14	108	258	-33	1a
XTeer IGO EP VG 220	0.8730	201.5	19.04	107	262	-13	1a
XTeer IGO EP VG 320	0.8760	307.4	26.2	112	264	-12	1a
XTeer IGO EP VG 460	0.8780	421.9	33.0	114	276	-12	1a
XTeer IGO EP VG 680	0.8920	664.4	40.4	102	260	-10	1a