

XTEER R&O

Industrial Lubricants – Hydraulic fluid

Description

XTeer R&O is a rust and oxidation inhibited hydraulic oil. It is formulated with select additives and designed for use in a variety of industrial applications. It is also suitable for use in applications where a premium R&O product is not required.

Application

- ✧ Applications where a straight mineral oil is required without extreme pressure (EP), detergent, dispersant or anti-wear additives.
- ✧ General machine oil
- ✧ Low pressure circulating fluid
- ✧ Non-Critical hydraulic applications
- ✧ Air-tool oil
- ✧ Drip or splash lubricant
- ✧ Spindle Oil
- ✧ Lubrication of light-duty compressors

Features / Benefits

- ✧ Protection against oxidation
- ✧ Protection against rust and corrosion
- ✧ Low foaming

Specification

XTeer R&O meets or exceeds the requirements of

- ✧ Parker Hannifin France HF-1,
- ✧ DIN 51524 Part 1, MIL-H-17672D
- ✧ U.S. Steel 126, AFNOR E46-800 HL

Product Name	Specific Gravity (15°C/4°C)	Kinematic Viscosity (cSt)		Viscosity Index	Flash Point (°C)	Pour Point (°C)
		@40°C	@100°C			
XTeer R&O VG 32	0.8589	31.75	5.43	106	232	-27.0
XTeer R&O VG 46	0.8615	45.93	6.94	108	238	-30.0
XTeer R&O VG 68	0.8657	65.87	8.75	105	250	-21.0